



www.XlntTint.com

Flat Glass Window Film Specifications



	NFRC Rated	Visible Light Transmission	Exterior Visible Light Reflection	Interior Visible Light Reflection	Solar Heat Gain Coefficient (*Shading Coefficient Only)	Glare Reduction	Ultra Violet Light Rejection (UV A/B)	Infrared Light Rejection (2400nm)	Infrared Light Rejection (780nm)	SPF Rating	Total Solar Energy Rejection
Huper Ceramic 30 (C30)	Yes	34%	11%	11%	0.37	62%	99.9%	85%	←	>200	63%
Huper Ceramic 40 (C40)	Yes	42%	9%	9%	0.45	53%	99.9%	80%	←	>200	53%
Huper Ceramic 50 (C50)	Yes	50%	10%	10%	0.50	45%	99.9%	68%	←	>200	50%
Huper Ceramic 60 (C60)		58%	9%	9%	0.58	34%	99.9%	60%	←	>200	42%
Huper Select Acht	Yes	77%	9%	9%	0.54	14%	99.9%	77%	←	>200	46%
Huper Select Sech	Yes	59%	8%	8%	0.46	34%	99.9%	83%	←	>200	54%
Huper Select Drei	Yes	35%	12%	12%	0.30	61%	99.9%	98%	←	>200	70%
Krystal View Ultra 15 (Kvu 15)		14%	54%	24%	0.23	85%	99%	N/A	N/A	N/A	79%
Krystal View Ultra 25 (Kvu 25)		27%	35%	20%	0.31	72%	99%	N/A	N/A	N/A	67%
Krystal View Ultra 35 (Kvu 35)		35%	27%	18%	0.37	58%	99%	N/A	N/A	N/A	60%
Krystal View Ultra 50 (Kvu 50)		47%	16%	12%	0.44	47%	99%	N/A	N/A	N/A	56%
Krystal View 20 (KV20)		16%	60%	58%	0.21	82%	99%	N/A	N/A	N/A	81%
Krystal View 35 (KV 35)		34%	44%	40%	0.35	61%	99%	N/A	N/A	N/A	70%
Harvest Bronze 20 (HB 20)		22%	37%	34%	0.22	75%	99%	N/A	N/A	N/A	78%
Harvest Bronze 35 (HB 35)		35%	25%	22%	0.30	60%	99%	N/A	N/A	N/A	70%
Hi Lite 70		72%	9%	9%	0.45	20%	99%	95%	←	N/A	55%
V-Kool 70 (VK 70)	Yes	70%	8%	N/A	N/A	N/A	99%	94%	←	N/A	55%
Night Vision 15 (NV 15)		15%	43%	19%	*0.29	83%	99%	N/A	N/A	N/A	75%
Night Vision 25 (NV 25)		24%	29%	13%	*0.39	72%	99%	N/A	N/A	N/A	66%
Night Vision 35 (NV 35)		35%	18%	12%	*0.49	60%	99%	N/A	N/A	N/A	57%
Night Vision 45 (NV 45)		45%	9%	8%	*0.63	49%	99%	N/A	N/A	N/A	45%
Clear Glass		88%	8%	8%	0.94		38%				18%

All specifications taken from published specification sheets from the respected manufacture

©Xlnt Tint 2008

